

Description

Lotrène® Q1018 N is an ethylene-butene copolymer produced in a gas phase reactor. It is designed for delivering competitive performance in most blown film applications.

Lotrène® Q1018 N can be processed at high output rates with moderate extrusion pressure, good bubble stability and gauge control on blown film machine designed for LLDPE.

Lotrène® Q1018 N can advantageously be blended with LDPE or other PE resins used in blown film mono extrusion or coextrusion to improve film properties.

Lotrène® Q1018 N is suited for many applications in the field of consumer, industrial, food or hygiene packaging such as collation shrink, liners, Form-Fill-Seal, heavy-duty sacks, refuse sacks or other bags and non-packaging applications like agricultural films e.g. tunnel and mulching films.

Characteristics

Property	Method	Unit	Typical value
Density (*)	ASTM D-792	g/cm ³	0.918
Melt Flow Rate (190°C/2.16 kg)	ASTM D-1238	g/10 min	1.0
Melting temperature	Internal method	°C	122
Vicat softening point	ASTM D-1525 (A120)	°C	100

(*) Density as measured on base resin.

Values indicated are typical for this product. Density and MFR are properties routinely measured during "the standard quality control procedure". Other figures are generated by tests not included in the "standard quality control procedure". They are given for information only and are not intended for specification purposes.

Processing

Lotrène® Q1018 N is typically extruded at a melt temperature around 200°C.

Lotrène® Q1018 N can be blown in the following conditions on machine designed for LLDPE:

- >> Extrusion temperature: 180 to 220°C
- >> BUR: 2:1 to 3:1
- >> Die gap: > 1.8 mm

It is recommended to maintain extrusion temperature below 240°C.

An excellent blending of Lotrène® Q1018 N with LDPE and HDPE and mLLDPE was observed.

Information contained in this publication is true and accurate at the time of publication and to the best of our knowledge. The nominal values stated herein are obtained using laboratory test specimens. Before using one of the products mentioned herein, customers and other users should take all care in determining the suitability of such product for the intended use. Unless specifically indicated, the products mentioned herein are not suitable for applications in the pharmaceutical or medical sector. The Companies within Total Petrochemicals do not accept any liability whatsoever arising from the use of this information or the use, application or processing of any product described herein. No information contained in this publication can be considered as a suggestion to infringe patents. The Companies disclaim any liability that may be claimed for infringement or alleged infringement of patents.

Additives

Antioxidant: yes
 Processing aid: no
 Slip agent: no
 Antiblock agent: no

Blown film properties

These values have been measured on a 40 µm film.

	Method	Unit	Typical value (*)
Tensile Strength at Yield MD/TD	ISO 527-3	MPa	11/11
Tensile Strength at Break MD/TD	ISO 527-3	MPa	38/33
Elongation at Break MD/TD	ISO 527-3	%	800/850
Elmendorf MD/TD	ISO 6382-2	N/mm	70/120
Secant modulus at 1% MD/TD	ISO 178	MPa	215/245
Dart test, F50	ISO 7765-1	g	150
Haze	ISO 14782	%	11
Gloss 45°	ASTM D2457		60

(*) Figures stated here above are obtained using laboratory test specimens produced with the following extrusion conditions: 45 mm screw, L/D = 30, die = 120 mm, die gap = 2.2 mm, BUR = 2.5:1, temperature = 210°C. Figures are average values generated by tests that are not included in the "standard quality control" they are not intended for specification purpose.

Handling and storage

Please refer to the safety data sheet (SDS) for handling and storage information. It is advisable to convert the product within one year after delivery provided storage conditions are used as given in the SDS of our product. SDS may be obtained from the website: www.polymers.total.com

Information contained in this publication is true and accurate at the time of publication and to the best of our knowledge. The nominal values stated herein are obtained using laboratory test specimens. Before using one of the products mentioned herein, customers and other users should take all care in determining the suitability of such product for the intended use. Unless specifically indicated, the products mentioned herein are not suitable for applications in the pharmaceutical or medical sector. The Companies within Total Petrochemicals do not accept any liability whatsoever arising from the use of this information or the use, application or processing of any product described herein. No information contained in this publication can be considered as a suggestion to infringe patents. The Companies disclaim any liability that may be claimed for infringement or alleged infringement of patents.